



PRICE RESEARCH, LTD.
 3511 Stadium Drive
 Kansas City, Missouri 64129
 Phone/Fax (816) 924-5955
 www.priceresearchltd.com

PRODUCT DATA

PRICE - SEAL

● PROTECTS ● WATERPROOFS ● SEALS CONCRETE AND MASONRY SURFACES

PRODUCT NAME: PRICE - SEAL

MANUFACTURER: PRICE RESEARCH, LTD.
 3511 Stadium Drive
 Kansas City, MO 64129
 Phone: (816) 924-5955

PRODUCT DESCRIPTION:

PRICE - SEAL is a unique blend of polymer, combined with evaporating media to provide a high performance, non-yellowing, long lasting protection coating.

Basic Use:

- Invisible water barrier for brick masonry.
- Excellent for concrete masonry protection.
- Minimize or eliminate efflorescence.
- Spalling and cracking are reduced or eliminated.
- Provides self-cleaning exterior surfaces.
- Lets masonry breathe.
- Excellent for tile, stucco, architectural concrete, etc.
- Provides mildew and fungus resistance.
- Excellent for exterior and interior surfaces (vertical and horizontal).
- Excellent concrete curing agent (Price-Seal (floor sealer), Price-Seal 15, Price-Seal 20 and Price-Seal 25).
- Excellent protection against animal waste and urine.

Meets and surpasses Fed. Spec. SS-W-110 b (GSA-FSS) Performance.
 PRICE - SEAL 20 and PRICE - SEAL 25 meets and surpasses ASTM Spec. C-309 Type 1.

Composition and Materials:

PRICE -SEAL is a blend or high molecular polymer combined with high grad petroleum solvent.
 (Meets Rule #66)

SIZES:

PRICE - SEAL is packaged in factory sealed 5 gallon and 55 gallon containers

TECHNICAL DATE:

Color Water Clear
 pH Neutral
 Drying Time To touch, about 25 minutes
 Cold Stability Excellent (viscosity change)
 Flash Point 105°F (tag closecup)

Dry film characteristics: (Resistance to)

Acid Excellent
 Alkali Excellent
 Gasoline Excellent

Continued on back

Food Acid	Excellent
Airborne Pollutant	Excellent
Ultraviolet resistance	Excellent
Hydraulic Fluid	Excellent

GUIDE FOR PRODUCT SELECTION:

Various solids percentages are available in PRICE - SEAL protection system to provide desired effect.

PRICE - SEAL (Floor Sealer): For industrial floors, heavy traffic area. Basement areas, as curing membrane. Concrete hardening, dust proofing, good for concrete, terrazzo, brick floors.

PRICE - SEAL 5: For brick, steel troweled concrete or other low absorption masonry surfaces.

PRICE - SEAL 7 1/2: Exposed aggregate and pre-cast concrete sealer. All purpose use. Excellent for poured in place.

PRICE - SEAL 10: Heavy duty PRICE - SEAL. For tilt up. Provides slight gloss on pre-cast.

PRICE - SEAL 15: Heavy gloss on exposed aggregate and pre-cast. Very good concrete cure.

PRICE - SEAL 20: Heavy coating, glossy surface. Provides depth to matrix. Use in halls, around elevators and bathrooms. Excellent concrete cure. Meets ASTM Spec. C-309 Type 1 also meets AASHTO-M-148 type 1D.

PRICE - SEAL 25: Wet look, tile like appearance. Excellent concrete cure. Meets ASTM Spec. C-309 Type 1 also meets AASHTO-M-148 Type 1D.

INSTALLATION: TEST FIRST

Application:

- A. Repair all cracks and repaint joints. Dirt and loose particles should be removed from the surface to be treated.
- B. The surface to be treated must be dry. PRICE - SEAL may be applied with a brush, roller or spray. Coat surface uniformly, leaving no pinholes or gaps, at rate shown on the coverage table below. Under normal conditions, surface will dry in 30 minutes.
- C. When spraying, apply fine mist coat first to break surface tension. Go over with coarse second coat thoroughly saturating masonry. Using brush or roller, two coats are recommended. Clean all tools and equipment with mineral spirit.

For Horizontal & Vertical Surfaces:

Avoid applying in direct sun or on very hot day. Use short nap roller. flat short nap wool applicator is recommended for smooth concrete surface.

COVERAGE TABLE		
Type of Surface	Approximate Coverage (Sq.Ft. / Gal.)	Suggested Application
Brick Masonry	75 - 100	Two Coats
Exposed Aggregate	75 - 125	Two Coats
Concrete Walls (above grade)	100 - 150	Two Coats
Pre-Cast (smooth)	150 - 200	Two Coats
Stucco	75 - 100	Two Coats
Blocks	50 - 75	Two to Four Coats
Stone and Tile	200 - 300	Two Coats

NOTE: PRICE - SEAL masonry protection system does not bridge structural defects, cracks, etc.. Coverage will vary with the density, porosity, workmanship or masonry surface.

AVAILABILITY AND COST:

Please contact Price Research, Ltd. at (816) 924-5955.

LIMITED GUARANTEE:

Price Research, Ltd. has no control over the storage, handling or use of this product, this the guarantee is limited to the purchase price of the defective material only.

TECHNICAL SERVICES:

Call (816) 924-5955 and ask for Technical Service.