

# RUST- KOTE

## DIRECTIONS FOR USE:

1. DO NOT dilute or alter package product.
2. Mix well before using.
3. No sanding of metal required, but wire brush lightly for best results. Clean off oil, dirt and grease before application.
4. Use rubber gloves.
5. Application is recommended between 50°F to 90°F.
6. Brush or sponge liberally, careful application will result in smooth finish.
7. Black coating will begin to develop in a few minutes. Uneven color indicates additional application is required for maximum protection. Two coats are usually required. Apply second coat after 1 to 2 hour wait.
8. Take enough material application container to finish job. Do not return unused material to original product container.
9. For long term protection and smoother finish, use sandable primer and paint. Do not sand black coating directly. Allow to dry 24 hours before painting.
10. Clean up with water and detergent.

RUST-KOTE is a new development in destroying old rust and the prevention of new rust on metal surfaces.

## ADVANTAGES:

- No sanding of metal required
- Long lasting
- Easy to use
- Metal may be painted over after treatment

## KEEP FROM FREEZING

## KEEP OUT OF REACH OF CHILDREN

## CAUTION:

Contains synthetic resin. Avoid contact with skin and eyes. For eye contact, flush with water for 15 minutes and get prompt medical attention. In case of skin contact, wash off immediately with water. If swallowed, induce vomiting and call a physician.

## EXCELLENT FOR:

- Machine Shops
- Industry
- Farm Equipment
- Any Rusty Surface
- Waste Treatment Plant
- City & County Garage
- Construction Equipment
- Hospitals
- Homes

**LIMITED WARRANTY:** PRICE RESEARCH, LTD. has no control over the storage, handling or use of this product. Thus the warranty is limited to the purchase price of the defective material only.

## PRICE RESEARCH, LTD.

3511 Stadium Drive  
Kansas City, MO 64129  
[www.priceresearchltd.com](http://www.priceresearchltd.com)

## NET CONTENTS

\_\_\_\_\_ GALLONS

Code: M-141

