



PRICE RESEARCH, LTD.
 3511 Stadium Drive
 Kansas City, Missouri 64129
 Phone/Fax (816) 924-5955
 www.priceresearchltd.com

PRODUCT DATA

PRICE GRAFFITI COATING

PRODUCT NAME: PRICE GRAFFITI COATING

MANUFACTURER: PRICE RESEARCH, LTD.
 3511 Stadium Drive
 Kansas City, MO 64129
 Phone: (816) 924-5955

PRODUCT DESCRIPTION:

PRICE GRAFFITI COATING is specially designed to protect masonry surfaces against graffiti defacement and easy removal. This system works well on brick, concrete and stone masonry to protect against graffiti markings.

Composition and Materials:

PRICE GRAFFITI COATING is composed of high molecular complex methacrylate resin in suitable hydrocarbon solvent with application plasticizer.

Recommended For:

- Brick Masonry
- Concrete Masonry
- Stone Masonry
- Any Masonry Surface

Limitations:

- Not suitable for asphaltic surfaces.
- Not recommended to be used at, or below, 50° F temperature.
- Test all surfaces for suitability (has good adhesion to glass surfaces).
- Keep off glass surface or clean immediately.

TECHNICAL DATA:

Form	Liquid
Flash Point	105° F
Shelf Life	6 months
Active Solids (ASTM-D 2834)	30%
V.O.C. Content (ASTM-3960)030 lbs/gal
Melting Point °F (ASTM-766)	165 ± 5

DIRECTION FOR USE: TEST FIRST

For Clean Masonry: Apply PRICE GRAFFITI COATING with brush, roller or sprayer (20 psi).
For Spray: When using low-pressure equipment, apply a light mist coat to break the surface tension. This allows for good penetration. Repeat the process with flood coat (4 to 6 inches run down).
NOTE: Do not alter material as supplied in container. Sprayers should be fitted with solvent resistant hoses and gaskets. Hand held "Hudson Type" sprayer or low-pressure (20 psi) sprayer are recommended for application.

Continued on back

For Graffiti Coated Masonry: Remove the graffiti with PRICE STRIP ALL GEL. Follow up with PRICE RESTORATION CLEANER to clean the masonry wall. Let the surface dry thoroughly. Follow label directions. Follow above application method to coat the surface.

NOTE: Graffiti Coating will protect masonry against all types of paint. Graffiti removal should be done with heavy duty detergent or solvent cleaner. Protection will last depending upon type of cleaning method used.

Coverage Rate:

Exact coverage will depend upon the porosity of the surface and density.

Concrete (broom finish)	100 sq.ft. / gal.
Concrete (smooth)	125 - 175 sq.ft. / gal.
Concrete Block	75 sq.ft. / gal.
Brick Masonry	100 sq.ft. / gal.

Clean Up:

Use xylene to clean tools and equipment.

Precautions:

- Use in well ventilated areas only.
- Do not dilute or alter PRICE GRAFFITI COATING.
- Protect glass and other non-masonry surfaces.
- Do not use at temperatures below 50°F.
- Product is flammable. Use with caution with spark, heat and handling.

AVAILABILITY AND COST:

Please contact Price Research, Ltd.
Phone: (816) 924-5955

LIMITED WARRANTY:

Price Research, Ltd. has no control over the storage, handling or use of this product, thus the guarantee is limited to the purchase price of the defective material.

TECHNICAL SERVICE:

Call Price Research, Ltd. at (816) 924-5955 and ask for Technical Service.