



**PRICE RESEARCH, LTD.**  
 3511 Stadium Drive  
 Kansas City, Missouri 64129  
 Phone/Fax (816) 924-5955  
 www.priceresearchltd.com

# PRODUCT DATA

## PRICE HEAVY DUTY RESTORATION CLEANER

**PRODUCT NAME:** PRICE HEAVY DUTY RESTORATION CLEANER

**MANUFACTURER:** PRICE RESEARCH, LTD.  
 3511 Stadium Drive  
 Kansas City, MO 64129  
 Phone: (816) 924-5955  
 www.priceresearchltd.com

**PRODUCT DESCRIPTION:**

PRICE HEAVY DUTY RESTORATION CLEANER is specially formulated to clean old brick, masonry, granite, terra-cotta, sandstone, etc.. It removes old weathering, dirt, carbon, algae, soot, mud, etc.. For limestone and concrete use Price Limestone Cleaner.

**Limitation:**

All masonry and non-masonry surfaces should be tested before application. For high rise building cleaning, use protection against traffic, protect plants and shrubs from direct contact.

**Composition and Materials:**

PRICE HEAVY DUTY RESTORATION CLEANER is a blend of organic and inorganic acid, with synergetic surfactant coupled with inhibitors.

**Size:**

5 gallon pail, 15 gallon and 55 gallon plastic drum.

**TECHNICAL DATA:**

Color . . . . . Water white  
 Specific Gravity. . . . . 1.2

**APPLICATION:**

1. Protect all non-masonry surfaces. Use Price Research Glass Protector for glass and aluminum surfaces.
2. PRICE HEAVY DUTY RESTORATION CLEANER may be applied with a fibered masonry brush or with low pressure spray (50 psi or less).
3. Applicators should wear the following: full rain suit of plastic, rubber or PVC, rubber boots and rubber goggles.
4. Pre-wet the wall. Apply PRICE HEAVY DUTY RESTORATION CLEANER. Determine dilution from prior testing. Let set for 3 to 5 minutes. Re-apply diluted PRICE HEAVY DUTY RESTORATION CLEANER. Rinse off from the bottom up with 400 to 500 psi water pressure (3 to 5 gallons per minute, 40° fan tip recommended). Rinse until absence of foaming on the wall.

Prior testing should indicate the necessity of a second application and dilution rate.

**NOTE:** Do not apply PRICE HEAVY DUTY RESTORATION CLEANER with high pressure spray. 50 psi or less is recommended.

**FOR BEST RESULTS:**

1. Test sample on masonry wall prior to general cleaning.

Continued on back

2. Protect non-masonry surfaces. Avoid drift and protect shrubs from direct contact.
3. Protect glass and aluminum surfaces with Price Mask.
4. Use rubber gloves, eye protection and rubber apron or coat. Petroleum jelly may be applied on face for skin protection.
5. Use of water pressure 400 to 500 psi, with 40° fan tip nozzle recommended.

**COVERAGE:** Actual coverage will depend upon the types of masonry, condition, skill of labor, etc.. Theoretical coverage is 100 sq.ft./gallon concentrate.

**TECHNICAL SERVICE:** Contact Price Research, Ltd. at 816-924-5955.

**LIMITED GUARANTEE:**

Price Research, Ltd. has no control over the storage, handling, or use of this product, thus the guarantee is limited to the purchase price of defective material only. All information and directions as contained in this bulletin and on product label are intended for use by persons having experience and practical application skills.