

PRICE LIMESTONE RESTORER

PRODUCT NAME: PRICE LIMESTONE RESTORER

MANUFACTURER: PRICE RESEARCH, LTD.

3511 Stadium Drive Kansas City, MO 64129 Phone: (816) 924-5955

PRODUCT DESCRIPTION:

PRICE LIMESTONE RESTORER is specially designed to clean limestone (Indiana limestone, etc.) and any high calcium based limestone, including man made limestone. PRICE LIMESTONE RESTORER works excellently on exposed aggregate concrete panels.

Limitations:

All masonry and non-masonry surfaces should be tested before application. For high-rise building cleaning, use protection against traffic. Protect plants and shrubs from direct contact.

Composition and Materials:

PRICE LIMESTONE RESTORER is a blend of organic and inorganic acid, with synergetic surfactant coupled with inhibitors.

Available Sizes:

5 gallon pail; 15 gallon and 55 gallon plastic drums.

TECHNICAL DATA:

ColorWater whiteSpecific Gravity1.07 (water 1.0) $\pm .03$

APPLICATION: TEST FIRST

- 1. Protect all non-masonry surfaces.
- 2. PRICE LIMESTONE RESTORER may be applied with fibered masonry brush or with low pressure spray.
- 3. Pre-wet the wall. Apply PRICE LIMESTONE RESTORER. Let set for two to three minutes. Re-apply PRICE LIMESTONE RESTORER. Rinse off from bottom up with maximum water pressure. Use high water pressure, if available. Rinse until absence of foaming on the wall.
- **4.** Prior testing should indicate the necessity of second application and dilution rate.

Continued on back

Coverage:

Actual coverage will depend upon the type of masonry, condition, skill of labor, etc.. Theoretical coverage is 100 square feet per gallon.

AVAILABILITY AND COST:

Contact Price Research, Ltd. at (816) 924-5955.

TECHNICAL SERVICES:

Contact Price Research, Ltd. at (816) 924-5955 and ask for Technical Service.

LIMITED GUARANTEE:

Price Research, Ltd. as no control over the storage, handling or use of its products, thus the guarantee is limited to the purchase price of defective material only. All information and directions as contained in this bulletin and on the product label are intended for use by persons having experience and practical application skill.

FOR BEST RESULTS:

- Test sample on masonry wall prior to general cleaning.
- Protect non-masonry surfaces. Avoid drift and protect shrubs from direct contact.
- Protect glass and aluminum surfaces with PRICE ACID-STOP.
- Use rubber gloves, eye protection and apron. Petroleum jelly may be applied on face for skin protection.
- Use of water pressure, 400 to 600 psi, with adjustable nozzle is recommended.