



PRICE RESEARCH, LTD.
3511 Stadium Drive
Kansas City, Missouri 64129
Phone (816) 924-5955
www.priceresearchltd.com

PRODUCT DATA

PRICE SEAL-WB **(V.O.C. Compliant)** **WATERBASE WATERPROOFING FOR CONCRETE MATERIAL**

PRODUCT NAME: PRICE SEAL-WB (V.O.C. Compliant)
Waterbased Waterproofing for Concrete Material

MANUFACTURER: PRICE RESEARCH, LTD.
3511 Stadium Drive
Kansas City, MO 64129
Phone: (816) 924-5955

PRODUCT DESCRIPTION:

PRICE SEAL-WB is a penetrating sealer designed to protect concrete surfaces, decks, pavements, parking structures, ramps, etc.. PRICE SEAL-WB protects against corrosive adverse effects of deicing salts, moisture, weathering, spalling and sealing of concrete.

Composition and Materials:

PRICE SEAL-WB is composed of high molecular copolymer of vinyl acrylate in the aqueous solution.

Features:

- Provides protection against spalling.
- Provides protection against moisture.
- Dries tack free and skid-resistance surfaces.
- Long lasting protection for new as well as old concrete.

Recommended For:

- Any Concrete Structures ● Parking Structures ● Lane Barriers
- Hard To Reach Closed Areas ● Brick Masonry ● Concrete Blocks - all types ● Stone Masonry

Advantages:

- PRICE SEAL-WB is a waterbase product. Thus air pollution is minimal.
- Safer to use in closed areas.
- Completely non-flammable.
- Breathable coating.
- V.O.C. Compliant.
- Long lasting protection.

LIMITATIONS:

PRICE SEAL-WB is a freezable material. Use recommended at 50°F or above.

Continued on back

TECHNICAL DATA:

Type	High molecular vinyl acrylate copolymer
Flash Point	None
Shelf Life	1 year (close container at room temperature)
Active Solids	25%
Chloride Screened	Excellent
Repellency Factor	Very Good
Water Absorption	Minimum
Scaling Resistance	Excellent

DIRECTION FOR USE: TEST FIRST

New Concrete:

Surface should be well cured. Surface should be free of all dust, debris, oil and tar. All joint sealants, caulks and patching should be in place before applying PRICE SEAL-WB.

Old Concrete:

Remove dirt, tar, oil, etc.. Remove loose, spall concrete before sealing.

APPLICATION: TEST FIRST

Equipment:

Roller, brush or low pressure sprayer.

Horizontal and Vertical Surfaces:

Apply PRICE SEAL-WB with fine mist and then follow up with coarse spray over same area evenly. Surface should be covered evenly. For vertical surface, let it run down 4 -6 inches. Follow coverage table closely for long lasting protection.

Coverage Rate:	
Concrete (broom finish)	150 - 200 sq.ft. / gal.
Concrete (smooth finish)	200 - 250 sq.ft. / gal.
Exposed Aggregate	175 - 200 sq.ft. / gal.
Concrete Block	75 - 100 sq.ft. / gal.
Concrete Block - Split Face	75 - 100 sq.ft. / gal.
Brick Masonry	175 - 200 sq.ft. / gal.
Stone Surface	100 sq.ft./gal.
Burnish Block	200 - 250 sq.ft. / gal.

Clean Up:

Use warm water and soap.

AVAILABILITY AND COST:

Please contact Price Research, Ltd.

Phone: (816) 924-5955

LIMITED WARRANTY:

Price Research, Ltd. has no control over the storage, handling or use of this product, thus the guarantee is limited to the purchase price of the defective material only. All information and direction, as contained in this bulletin and on the product label, are intended for use by persons having experience and practical application skill. No other guarantees/warranties are expressed or implied.

TECHNICAL SERVICE:

Call Price Research, Ltd. at (816) 924-5955 and ask for Technical Service.