



PRICE RESEARCH, LTD.
3511 Stadium Drive
Kansas City, Missouri 64129
Phone (816) 924-5955
www.priceresearchltd.com

PRODUCT DATA

PRICE PAVER COLOR ACCENT

PRODUCT NAME: PRICE PAVER COLOR ACCENT

MANUFACTURER: PRICE RESEARCH, LTD.
3511 Stadium Drive
Kansas City, MO, USA 64129
Phone: (816) 924-5955

PRODUCT DESCRIPTION:

PRICE PAVER COLOR ACCENT is specially design to protect and color enhance the variety of paver surfaces for horizontal surfaces as well as vertical.

Composition and Materials:

PRICE PAVER COLOR ACCENT is a product of advance development in silicone and silane chemistry combined with water carrier for environmental safety.

Features:

☐ Provide color accent. ☐ Provide depth of color. ☐ Enhances the natural color. ☐ Provides excellent water repellancy. ☐ Provides long term protection. ☐ Natural breathability. ☐ Provides alkaline resistance. ☐ Penetrates deep. NO FILM formation. ☐ Resists blushing in high humidity areas. ☐ Water base, safe to use. ☐ Controls efflorescence.

Excellent For:

- ☐ All kinds of paver and brick.
- ☐ Excellent for concrete paver use.
- ☐ Excellent for unpolished marble and granite.
- ☐ Excellent for natural color as well as color added units.

Recommended For:

1. Shopping Malls
2. Plaza Areas
3. Commerical Kitchens
4. Food Courts
5. Amusement Parks
6. Zoo
7. Sport Arenas
8. Driveways
9. Parking Structures
10. Restaurants

Limitations:

1. Not suitable for asphaltic surfaces.
2. Not recommended to be used at or below 40°F temperature.
3. Test all surfaces for suitability.
4. Protect glass, aluminum, etc..
5. Will not bridge gaps, cracks and structural defects.
6. Recommended to be used between 40°F and 90°F air and surface temperature.
7. Protect foliage, painted surfaces, etc..
8. Not recommended for polished marble, granite or slate.

Continued on back

TECHNICAL DATA:

Form	Liquid
Color	Milky liquid
Flash point	Over 300°F
Wt./gal.	8.3 lbs.
pH	Neutral
Odor	None

DIRECTIONS FOR USE: TEST FIRST

Surface Preparation:

Surface should be clean, dry and oil free. Use appropriate Price Research, Ltd. Masonry Cleaning Product before application. All joint sealant and caulks and patching should be in place before applying the product. Surfaces should be well cured using water, wet burlap, polyethylene or curing paper.

Equipment:

Roller, brush or low pressure spray (40 psi or less). Fan spray tips are recommended.

Horizontal Surfaces:

Flood surface using low pressure sprayer (airless sprayer 40 psi or less) roller, brush or broom. Broom or squeegee PRICE PAVER COLOR ACCENT around for even distribution. Let the surface absorb the solution and follow up immediately with a second application before the surface dries. Redistribute any puddles or free standing material.

Vertical Surfaces:

Apply by sprayer, roller or brush in two applications from bottom up. Be sure to apply 'wet on wet' method as described for horizontal surface. For vertical surfaces let the material run down 5 to 10 inches saturating the surface from contact point of spray. Follow up with second application before surface dries.

Coverage Rate

Exact coverage will depend upon the porosity of the surface and density.

Brick Pavers	100 - 150 sq.ft.
Concrete Blocks, Paver, etc.	75 - 125 sq.ft.
Colored Concrete Blocks, etc.	75 - 125 sq.ft.
Stone (limestone, marble, sandstone, granite, slate)	300 - 500 sq.ft.
Terrazzo	300 - 500 sq.ft.

NOTE: Not recommended for polished marble, polished granite or polished slate surfaces.

Clean Up: Clean tools and equipment with soap and water.

PRECAUTIONS:

1. Use in well ventilated areas only. **2.** Do not dilute or alter the material. **3.** Protect glass, metal and other non-masonry surfaces. **4.** Do not use over curing membrane. **5.** Initial cure will be in 24 hours. Maximum cure will require up to 7 days. **6.** Do not use at temperatures below 40°F (4°C).

AVAILABILITY AND COST:

Please contact Price Research, Ltd. at 816-924-5955.

LIMITED WARRANTY:

Price Research, Ltd. has no control over the storage, handling or use of this product, thus the guarantee is limited to the purchase price of the defective material only.

TECHNICAL SERVICES:

Call 816-924-5955 and ask for Technical Service.