



PRICE RESEARCH, LTD.
3511 Stadium Drive
Kansas City, Missouri 64129
Phone/Fax (816) 924-5955
www.priceresearchltd.com

PRODUCT DATA

STONE PROTECTOR

PRODUCT NAME: STONE PROTECTOR
A water based polysiloxane penetrating water repellent for natural stone, limestone and precast (breathable)

MANUFACTURER: PRICE RESEARCH, LTD.
3511 Stadium Drive
Kansas City, MO 64129
Phone: (816) 924-5955

PRODUCT DESCRIPTION:

Stone protector is a water based polysiloxane penetrating water repellent designed specifically for natural stone, limestone and precast substrates where darkening is unacceptable. Stone Protector reduces bonding of hydrocarbons, reduces water damage from freeze-thaw, protects against efflorescence and has excellent ultraviolet resistance.

APPLICATION: TEST FIRST

1. Surfaces to be treated should be free of dirt, airborne contaminants and moisture.
2. It is extremely important that the surface be completely dry.
3. New concrete should be allowed to cure at least 14 days before application of Stone Protector.
4. Stone Protector can be applied with low-pressure spray equipment, brush or roller.
5. When using low-pressure equipment apply a light mist coat to break surface tension. This allows for good penetration. Then repeat the process with a flood coat (4 to 6 inch run down).

Caution! Do not alter the material as supplied in the container. **Note:** A test panel should be preformed to insure compatibility.

PRODUCT LIMITATIONS:

- Air and surface temperatures must be above 40°F during application.
- Caulking should be installed prior to application of Stone Protector.
- Protect surrounding non-masonry surfaces, such as glass, aluminum, etc.
- Inadvertent splashes should be removed with water before the solution has dried on surface.
- Do not apply when rain is predicted within 24 hours.
- Store at room temperatures above freezing.

Continued on back

TECHNICAL INFORMATION:

Flash Point	None
Color (gardner)	2 Maximum
Odor	None
Weight	8.8 lbs. per. gallon
PH	8.7
Carrier	H2O

NOTE: Not recommended for dark surfaces.

COVERAGE RATE	
<u>Substrate</u>	<u>Sq. Ft. Per Gallon</u>
Natural Stone	100 - 125
Limestone	100 - 150
Smooth Precast	100 - 125
Rough Exposed Aggregate	80 - 125

GUARANTEE / WARRANTY:

Price Research, Ltd. warrants the quality and performance of this product when used according to directions and will replace this product if found to be defective. Price Research shall not be liable for cost of labor, direct, incidental or consequential damage. No other guarantees/warranties are expressed or implied.

TECHNICAL SERVICE:

Call Price Research, Ltd. at (816) 924-5955 and ask for Technical Service.